



1	BOLT, DRILLED (TORQUE TO 50 IN. LBS.)	.25-20X2BOLT(A)	2	10	PISTON, 5/6" BRAKE	PI-1	1	18	BRAKE DISC, 5" BRAKE	D5	1
2	BOLT	AN4-20A	2					19	SHCS, DRILLED (TORQUE 40 IN. LBS.)	.25-20X.62SHCS(A)	3
3	WASHER	AN960-416L	10	11	O-RING BUNA N	2-222	1	19A	WASHER	AN960-416	2
4	STATIONARY BRK SHOE, 5/6"	SBS5	1	12	PUCK HOUSING 5/6" BRK	PH-1	1	20	BOLT	AN4-22A	3
5	LINING, 5/6" BRAKE	M66-106	2	13	FLEX LOCK NUT, .25-28 (TORQUE 50 IN. LBS.)	AN363-428	3	21	DUST PLUG	.234-.50IL	1
6	BRASS RIVET	4-6	6	14	ROLLER BEARING, .75	LM11900LA	2	22	BRAKE BLEEDER VALVE	F6446-007	1
7	BRAKE PLATE, .75 AXLE	BPA.75	1	15	BEARING RACE, .75	LM11910	2	23	BRAKE BLEEDER SEAT	BBS(A)	1
8	SPACER, 5/6"	BSP5	4	16	VALVE HALF, W50, .75 BRNG	W50/.75	1	24	LOCK NUT (TORQUE TO 50 IN. LBS.)	.25-28NYLOC	2
9	MOVEABLE BRK SHOE, 5/6" BRK	MBS5	1	17	BRAKE HALF, W50S, .75 BRNG	B50S.75	1	25	CAPLUG	2X	1
								26			
NO.	PART NAME	INVENTORY NO.	REQ'D	NO.	PART NAME	INVENTORY NO.	REQ'D	NO.	PART NAME	INVENTORY NO.	REQ'D

TD-WH50R

MATCO mfg
 2361 S 1560 West
 WOODS CROSS, UT 84087 (801) 335-0582

W50S.75

DRAWN BY: GARY P. LANGFORD
 AUTHORIZED BY:

SCALE: NONE
 DATE: JULY 21, 1993

REVISION:
 A